KOHLER®


Features

- Vitreous china
- Elongated bowl
- Class Five_® flushing system
- Polished chrome trip lever
- Less seat and supply
- 12" (305 mm) rough-in
- 1.6 gpf (6 lpf)
- 2-1/8" (54 mm) glazed trapway
- 11-3/4" (298 mm) x 9-1/2" (241 mm) water area
- 30-3/8" (772 mm) x 17-13/16" (452 mm) x 31-7/16" (799 mm) [K-3818]
- 30-3/8" (772 mm) x 18-7/8" (479 mm) x 31-1/16" (789 mm) [K-3819]

Codes/Standards Applicable

Specified model meets or exceeds the following:

- ADA
- ICC/ANSI A117.1
- CSA B651
- *OBC*
- ASME A112.19.2/CSA B45.1
- Energy Policy Act of 1992



MEMOIRS® CLASS FIVE®

COMFORT HEIGHT_® TOILET

K-3818

Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Accessories

- 0: White
- CP: Polished Chrome
- PB: $Vibrant_{\ensuremath{\mathbb{R}}}$ Polished Brass
- Other: Refer to Price Book for additional colors/finishes

Specified Model

| Model | Description | Trip | Trip Lever Color | | /Finishes | | | |
|-------------------------|--|------|------------------|------|-----------|--|--|--|
| K-3818 | Comfort Height toilet with Classic design | left | hand | 0 🗆 | Other | | | |
| K-3819 | Comfort Height toilet with Stately design | left | hand | 0 🗆 | □ Other | | | |
| Recommended Accessories | | | | | | | | |
| K-4650 | Lustram elongated open-front seat – for Accessibility compliance | 0 🗆 | | | Other | | | |
| K-7637 | Angle supply with stop – 3/8" NPT | | CP | 🗆 PB | Other | | | |

Product Specification

The elongated bowl toilet shall be made of vitreous china. Toilet shall be 30-3/8" (772 mm) in length, 18-7/8" (479 mm) in width, and 31-1/16" (789 mm) in height [K-3819] or 30-3/8" (772 mm) in length, 17-13/16" (452 mm) in width, and 31-7/16" (799 mm) in height [K-3818]. Toilet shall have a 11-3/4" (298 mm) x 9-1/2" (241 mm) water area. Toilet shall be 12" (305 mm) rough-in with a 2-1/8" (54 mm) glazed trapway. Toilet shall be 1.6 gpf (6 lpf) with Class Five flushing system. Toilet shall include a polished chrome trip lever. Toilet shall be less seat and supply. Toilet shall be Kohler Model K-_____.

MEMOIRS_® CLASS FIVE_®

Optional Accessories

K-9167 Trip lever – non CP

Technical Information

| Fixture: | | | | | |
|------------------------------|---------------------------------------|-----------------|--|--|--|
| Configuration | two-piece, elongated | | | | |
| Water per flush | 1.6 gpf (6 lpf) | | | | |
| Passageway | 2-1/8" (54 mm) | | | | |
| Water area | 11-3/4" (298 mm) x 9-1/2" (241 mm) | | | | |
| Water depth from rim 6- | | (156 mm) | | | |
| Seat post hole centers | 5-1/2″ (| 5-1/2" (140 mm) | | | |
| Included components: | | | | | |
| Bowl | K-4380 | | | | |
| Tank with Classic design OF | K-4641 | | | | |
| Tank with Stately design | K-4642 | | | | |
| Tank cover with Classic desi | 1052861 | | | | |
| Tank cover with Stately desi | 1052862 | | | | |
| Trip lever | K-9167 | | | | |

| Included components: (cont.) | |
|------------------------------|---------|
| Bolt cap accessory pack | 1013092 |

D PB

Other

Installation Notes

Install this product according to the installation guide.

Will comply with the American Disabilities Act **(ADA)** when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act. The Model Plumbing Codes require the installation of elongated open-front toilet seats in public bathrooms.

Will comply with **CSA B651** when installed per Clause 4.3.6 of the standard.

Will comply with **OBC** Barrier Free requirements when installed per Clause 3.8.3.8 and 3.8.3.9.

