

MEMOIRS_® CLASS FIVE_®

Features

- Vitreous china
- Elongated bowl
- Class Five_® flushing system
- Polished chrome trip lever
- Less seat and supply
- 12" (305 mm) rough-in
- 1.28 gpf (4.8 lpf)
- 2-1/8" (54 mm) glazed trapway
- 11-3/4" (298 mm) x 9-1/2" (241 mm) water area
- 30-3/8" (772 mm) x 17-13/16" (452 mm) x 31-7/16" (799 mm) [K-3816]
- 30-3/8" (772 mm) x 18-7/8" (479 mm) x 31-1/16" (789 mm) [K-3817]

Codes/Standards Applicable

Specified model meets or exceeds the following:


- ADA
- ICC/ANSI A117.1
- CSA B651
- OBC
- ASME A112.19.2/CSA B45.1
- EPA WaterSense®

COMFORT HEIGHT® TOILET K-3816 ALSO K-3817

ADA CSA B651

OBC





Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Specified Model

| Model | Description | Trip Lever | Colors/ | Finishes |
|-----------|---------------------------------------------------------|------------|---------|----------|
| K-3816 | Comfort Height toilet with Classic design | left-hand | □0 | ☐ Other |
| K-3816-RA | Comfort Height toilet with Classic design | right-hand | □0 | ☐ Other |
| K-3816-U | Comfort Height toilet with Classic design and Insuliner | left-hand | □ 0 | ☐ Other |
| K-3817 | Comfort Height toilet with Stately design | left-hand | □ 0 | ☐ Other |
| K-3817-RA | Comfort Height toilet with Stately design | right-hand | □ 0 | ☐ Other |
| K-3817-U | Comfort Height toilet with Stately design and Insuliner | left-hand | □ 0 | ☐ Other |

| Recommended Accessories | | | | | |
|-------------------------|------------------------------------------------------------------|----|------|------|---------|
| K-4650 | Lustra™ elongated open-front seat – for Accessibility compliance | □0 | | | ☐ Other |
| K-7637 | Angle supply with stop – 3/8" NPT | | □ CP | □ PB | ☐ Other |

Product Specification

The elongated bowl toilet shall be made of vitreous china. Toilet shall be 30-3/8" (772 mm) in length, 18-7/8" (479 mm) in width, and 31-1/16" (789 mm) in height [K-3817] or 30-3/8" (772 mm) in length, 17-13/16" (452 mm) in width, and 31-7/16" (799 mm) in height [K-3816]. Toilet shall have a 11-3/4" (298 mm) x 9-1/2" (241 mm) water area. Toilet shall be 12" (305 mm) rough-in with a 2-1/8" (54 mm) glazed trapway. Toilet shall be 1.28 gpf (4.8 lpf) with Class Five flushing system. Toilet shall include a polished chrome trip lever. Toilet shall be less seat and supply. Toilet shall be Kohler Model K-_____-___.

MEMOIRS® CLASS FIVE®

| Optional A | ccessories | | |
|------------|---------------------|------|---------|
| K-9167 | Trip lever – non CP | □ PB | ☐ Other |

Technical Information

| Fixture: | |
|------------------------|------------------------------------|
| Configuration | two-piece, elongated |
| Water per flush | 1.28 gal (4.8 L) |
| Passageway | 2-1/8" (54 mm) |
| Water area | 11-3/4" (298 mm) x 9-1/2" (241 mm) |
| Water depth from rim | 6-1/8" (156 mm) |
| Seat post hole centers | 5-1/2" (140 mm) |

| Included components: | |
|------------------------------------------|---------|
| Bowl | K-4380 |
| Tank with Classic design OR | K-4433 |
| Tank with Stately design | K-4434 |
| Tank cover with Classic design OR | 1052861 |
| Tank cover with Stately design | 1052862 |
| Trip lever | K-9167 |
| | |

| Included components: (cont.) | |
|------------------------------|---------|
| Bolt cap accessory pack | 1013092 |

Installation Notes

Install this product according to the installation guide.

Will comply with the American Disabilities Act (ADA) when installed per the requirements of the Accessibility Guidelines, Section 604 Water Closets, of the Act. The Model Plumbing Codes require the installation of elongated open-front toilet seats in public bathrooms.

Will comply with **CSA B651** when installed per Clause 4.3.6 of the standard.

Will comply with \mbox{OBC} when installed per Clause 3.8.3.8 and 3.8.3.9.

